

12 Office & Kitchen>LED Linear Profiles Medium size

38150A/B/C



40W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices.

Complete with 1000mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions




Gallery



Accessories



050170



050170C/B

Related items



38150E/B

Physical Specification

Item Group	12 Office & Kitchen
Family	LED Linear Profiles Medium size
Order Code	38150A/B/C
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	1200mm
Width	70mm
Height	35mm
Surface Ceiling	Yes
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20

Light Source
Dimmable
Cable Length
F Mark

LED built in
No
300cm


Fitting

Input Type
Input Current
Voltage
Power(Watts)
IP Rating
Light Source
LED Type
LED Brand
LED Number

Constant Current
1000mA
36V
36W
IP20
LED built in
SMD 2835
Epistar
288

Gear

Gear Type
Input Voltage
50 Hz
60 Hz
Power(Watts)
Power Factor
Constant Current
1000mA
IP Rating
Safety Class
Dimmable
Brand
Protection

Led Driver
220-240V
Yes
Yes
30-42W
0,9
Yes
30-42V
IP20

No
BOKE
0

Illumination Data

Colour Temperature	4000K
Lumen Output	3400lm
Light Efficiency	85lm/W
CRI	90
Beam Angle	120°
Illumination Diagram	
UGR	19

Packing Info

Pcs/Carton	12
Barcode	5291889062394
HS Code	9405409900

Certification & Warranty

Warranty	3 Years
Weee Directive	Yes

switch to
one light!

