



12 Office & Kitchen>UGR19 Recessed LED Linear Profiles

38150AR/W/C



40W UGR19 Recessed linear with diffuser, ideal for offices.

Complete with 1000mA driver , 4pcs fixing clips, 4pcs connectors & 2pcs end cups.

Can be connected in line

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

|                   |                                    |
|-------------------|------------------------------------|
| Item Group        | 12 Office & Kitchen                |
| Family            | UGR19 Recessed LED Linear Profiles |
| Order Code        | 38150AR/W/C                        |
| Colour            | White                              |
| Material          | Aluminium                          |
| Diffuser Material | Plastic                            |
| Shape             | Rectangular                        |

|                    |        |
|--------------------|--------|
| Length             | 1210mm |
| Width              | 80mm   |
| Height             | 55mm   |
| Cutout Hole Width  | 1200mm |
| Cutout Hole Length | 68mm   |
| Recessed Ceiling   | Yes    |
| Depth Required     | 80mm   |
| Indoor             | Yes    |
| Adjustable         | No     |

Electrical Characteristics

|                  |                                                                                       |
|------------------|---------------------------------------------------------------------------------------|
| Gear             | Built In                                                                              |
| Fitting + Driver |                                                                                       |
| Input Voltage    | 220-240V                                                                              |
| 50 Hz            | Yes                                                                                   |
| 60 Hz            | Yes                                                                                   |
| Safety Class     |  |
| Power(Watts)     | 40W                                                                                   |
| IP Rating        | IP20                                                                                  |
| Light Source     | LED built in                                                                          |
| Dimmable         | No                                                                                    |
| F Mark           |  |

|               |                  |
|---------------|------------------|
| Fitting       |                  |
| Input Type    | Constant Current |
| Input Current | 1000mA           |
| Voltage       | 36V              |
| Power(Watts)  | 36W              |
| IP Rating     | IP20             |
| Light Source  | LED built in     |

|                  |                                                                                       |
|------------------|---------------------------------------------------------------------------------------|
| LED Type         | SMD 2835                                                                              |
| LED Brand        | Epistar                                                                               |
|                  |                                                                                       |
| Gear             |                                                                                       |
|                  |                                                                                       |
| Gear Type        | Led Driver                                                                            |
| Input Voltage    | 220-240V                                                                              |
| 50 Hz            | Yes                                                                                   |
| 60 Hz            | Yes                                                                                   |
| Power(Watts)     | 30-42W                                                                                |
| Power Factor     | 0,95                                                                                  |
| Constant Current | Yes                                                                                   |
| 1000mA           | 30-42V                                                                                |
| IP Rating        | IP20                                                                                  |
| Safety Class     |  |
| Dimmable         | No                                                                                    |
| Housing Material | Metal                                                                                 |
| Output Terminal  | Connector                                                                             |
| Brand            | BOKE                                                                                  |

Illumination Data

|                      |                                                                                       |
|----------------------|---------------------------------------------------------------------------------------|
| Colour Temperature   | 4000K                                                                                 |
| Lumen Output         | 3600lm                                                                                |
| Light Efficiency     | 90lm/W                                                                                |
| CRI                  | 90                                                                                    |
| Illumination Diagram |  |
| UGR                  | 19                                                                                    |

Packing Info

|            |               |
|------------|---------------|
| Pcs/Carton | 12            |
| Barcode    | 5291889063865 |

HS Code

9405409900

Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to  
**one light!**

