



14 Plafo>The LED Slim Plafo Range Round

67366/W/C



12W LED slim plafo, IP54, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	14 Plafo
Family	The LED Slim Plafo Range Round
Order Code	67366/W/C
Colour	White
Material	PC
Shape	Circular
Height	50mm
Diameter	250mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No

IK Rating	8
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	
Fitting	
Input Type	Constant Current
Input Current	160mA
Voltage	70V
Power(Watts)	11,2W
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
F Mark	
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes

60 Hz
Power(Watts)
Power Factor
Constant Current
Output
Voltage Range
IP Rating
Safety Class
Dimmable
Housing Material
Output Terminal

Yes
12W
0,9
Yes
160mA
70V
IP20

No
Plastic
Cable

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram

4000K
960lm
80lm/W
80
120°


Packing Info

Box Length
Box Width
Box Height
Box Weight
Pcs/Carton
Carton Length
Carton Width
Carton Height
Carton Weight

26cm
26cm
5,7cm
0,8kg
20
60cm
54cm
29cm
16,1Kg

Barcode	5291889043041
HS Code	9405104090

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to
one light!

