



New 2021 Edition 2>Wall & Ceiling LED

67516A/W/W



15W COB LED cylinder, IP65, suitable for indoor and outdoor installation.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group
Family
Order Code
Colour
Material
Shape
Height
Diameter
Surface Ceiling
Indoor
Outdoor

New 2021 Edition 2
Wall & Ceiling LED
67516A/W/W
White
Aluminium
Circular
127mm
83mm
Yes
Yes
Yes

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	36V
Power(Watts)	12,6W
IP Rating	IP65
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	10,8-16W
Power Factor	0,9

Constant Current
400mA
IP Rating
Safety Class
Dimmable
Housing Material
Brand

Yes
27-40V
IP20

No
Plastic
KEGU

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram
Dark Light

3000K
1200lm
80lm/W
90
40°

Yes

Packing Info

Box Length
Box Width
Box Height
Pcs/Carton
Barcode
HS Code

9cm
9cm
16cm
24
5291889070108
9405409900

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

