



19 Wall Recessed & Inground>The Dark Light Inground Range

69056A/W



3W COB LED inground, IP67.

Requires 24V driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Must be ordered separately



89015V

Physical Specification

Item Group	19 Wall Recessed & Inground
Family	The Dark Light Inground Range
Order Code	69056A/W
Colour	Aluminium
Material	Natural Aluminium
Diffuser Material	Glass

Shape	Circular
Height	55mm
Diameter	55mm
Cutout Hole Diameter	50mm
Inground	Yes
Depth Required	100mm + 300mm drainage
Indoor	Yes
Outdoor	Yes
IK Rating	8

Electrical Characteristics

Fitting

Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	3W
IP Rating	IP67
Light Source	LED built in
LED Type	COB
LED Brand	Prolight
Cable Length	200cm
F Mark	

Illumination Data

Colour Temperature	3000K
Lumen Output	240lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	38°

Illumination Diagram



Dark Light

Yes

Packing Info

Pcs/Carton

50


Barcode

5291889064275

HS Code

9405409900

Energy Label



Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to
one light!

