




230V Waterproof Square Neonflex 9W/m, IP65 .

Supplied in 50m rolls.

Can be cut every 1m.

Complete power supply 7864P.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Accessories



7864C



7864E



7864F



7864P

Physical Specification

Item Group
Family
Order Code
Material
Shape

08 Strips & Profiles
230V Flex Lightline
7864/W
PVC
Rectangular

Length	50000mm
Width	8mm
Height	12mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	9W/m
IP Rating	IP65
Light Source	LED built in
Dimmable	Yes
Dimmer type	Triac
F Mark	

Fitting	
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

LED Number	120LEDs/m
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	450W
Power Factor	0,9
IP Rating	IP65

Illumination Data

Colour Temperature	3000K
Lumen Output	270lm
Light Efficiency	30lm/W
CRI	80
Illumination Diagram	

Packing Info

Pcs/Carton	50
Barcode	5291889066507
HS Code	9405403990

Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

