



Festoon light | 10m | 20pcs E27 socket | excl. power cord



Tronix festoon lights are made from high quality rubber cables. This not only gives you a flexible cable, but also a set that can withstand changing weather conditions. This ensures a longer lifespan and is ideal for decorating objects or facades.

In addition, our professional festoon lights feature rubber sealing rings. These provide a watertight seal between the sockets and the lamp, so that both parts are optimally protected.

Features

- IP65 (cable and sockets), IP44 (female/male connector with end cap)
- Professional set of festoon lights, made of high-quality rubber and equipped with sturdy, molded sockets. Supplied without lamps
- Connectable up to 200 meters / 2000W

Article number:	585-105
CHANGED_LAST:	30-04-2024
Brand:	Tronix Lighting
Type:	Festoon lighting
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC002761 - Festive lighting
SYNONYM:	Bulb luminaire, Candle, Candle stick light, Chandelier, Christmas lighting, Christmas tree lighting, Curtain light, Festive lighting, Illumination cable set





Feature

Model:	Illumination cable set	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Number of light points:	20	Constant light output (CLO):	No
Lamp type:	LED exchangeable	Degree of protection (IP):	IP65
With light source:	No	Protection class:	II
Colour:	Other	Fire resistance according to UL94:	C
Voltage type:	AC	Colour of light:	Other
Nominal voltage:	220 ~ 240 V	Power factor:	1
Connected load:	2500 W	Width:	0 mm
Battery power supply:	No	Height/depth:	0 mm
Suitable for outdoor use:	Yes	Total length:	10 m
With power bridge:	No	Diameter:	0 mm
Couplable:	Yes	Type of wiring:	Through wiring included
Type of control gear:	Not required	Number of poles:	2
Exchangeable control gear:	No	Conductor cross section:	1.5 mm ²
Rated life time L70/B50 at 25 °C:	0 h	Connection type:	Other
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %		

Packaging data

Weight	2.05 kg
Width	160 mm
Height	155 mm
Length	305 mm
Customs code	8544429090

