



New 2025 Edition 3>Industrial & Floodlights

7028CF/B/V



200W DOB LED CCT Variable floodlight with adjustable mounting bracket.

IP65 rated for outdoor use.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group
Family
Order Code
Colour
Material
Diffuser Material
Shape
Length
Width
Height
Surface Ceiling
Surface Wall

New 2025 Edition 3
Industrial & Floodlights
7028CF/B/V
Black
Aluminium
Glass
Rectangular
380mm
315mm
32mm
Yes
Yes

Surface Floor/Ground
Outdoor
Adjustable
IK Rating

Yes
Yes
1 Direction
6

Electrical Characteristics

Gear
Fitting + Driver
Input Voltage
50 Hz
60 Hz
Safety Class
Power(Watts)
IP Rating
Light Source
Dimmable
F Mark

Built In
220-240V
Yes
Yes

200W
IP65
LED built in
No


Fitting
Light Source
LED Type
Cable Length

LED built in
SMD
50cm

Gear
Gear Type
Input Voltage
Dimmable

Led Driver
220-240V
No

Illumination Data

Colour Temperature	3000K-4000K-6500K
Lumen Output	20000lm
Light Efficiency	100lm/W
CRI	80
Beam Angle	110°
Illumination Diagram	

Packing Info

Certification & Warranty

Warranty	2 Years
Average Lifetime	36000Hrs L70B50
Weee Directive	Yes

switch to
one light!

one
LIGHT

